LG Water Solutions



QuantumPure™

Product Data Sheet

Mixed Bed IX Resins

LG QuantumPure™ offers a comprehensive range of high-performance Ion Exchange (IX) resins, designed to meet a wide range of water treatment needs from deionization and softening to selective ion removal. Produced using state-of-the-art manufacturing processes, LG QuantumPure™ IX resins deliver consistent quality, excellent chemical resistance, and extended service life, reducing the need for frequent replacements and maintenance.



Key Features

- Mixed resin with equivalent amounts of cations and anions
- · Good operational stability



Key Benefits

- · Cost-effective water treatment
- · Removal of both cations and anions
- Ready-to-use



Key Applications

- Demineralization
- Condensate polishing
- · RO permeate water polishing
- · Boiler feed water

Physical and Chemical Properties

Product Name		QuantumPure™ GMB-200		QuantumPure™ GMB-210		QuantumPure™ GMB-300	
Matrix		Styrene-divinylbenzene, Gel					
Functional Group		Sulfonic acid	Type 1 (Trimethylammonium)	Sulfonic acid	Type 1 (Trimethylammonium)	Sulfonic acid	Type 1 (Trimethylammonium)
Ionic Form		H⁺	OH ⁻	H⁺	OH-	H⁺	OH ⁻
Average Diameter (µm)		300–1,200	300–1,200	300–1,200	300–1,200	300–1,200	300–1,200
Uniformity Coefficient		≤1.6	≤1.6	≤1.6	≤1.6	≤1.6	≤1.6
Ionic Conversion (%)	H⁺	99.0 Min	-	99.0 Min	-	99.0 Min	-
	OH ⁻	-	90.0 Min	-	95.0 Min	-	95.0 Min
	Cl	-	1.0 Max	-	1.0 Max	-	1.0 Max
Mixed Ratio		1:1 (by equivalents) Cation : Anion		1:1 (by equivalents) Cation : Anion		1:1 (by equivalents) Cation : Anion	
Inlet Condition	Water Type	Potable Water		Potable Water		Potable Water	
	Specific Flow Rate	SV36		SV36		SV36	
	Conductivity	150 µs/cm		150 µs/cm		10 μs/cm	
Outlet Condition	Resistivity	Guaranteed 10.0 MΩ·cm↑ (in 10min.) Actual 15.0 MΩ·cm↑ (in 10min.)		Guaranteed 10.0 MΩ·cm↑ (in 10min.) Actual 15.0 MΩ·cm↑ (in 10min.)		Guaranteed 15.0 MΩ cm↑ (in 10min.) Actual 17.0 MΩ cm↑ (in 10min.)	

Recommended Operating Conditions

Operating Temp (°C) [°F]	60
Min. Bed Depth (mm)	600
pH Range	0–14
Service Flow Rate (m/h)	5–60

^{*}The values specified are for reference only and does not guarantee performance.

The product performance is expressly conditioned on Buyer's storing, installing, operat ing, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at www.lgwatersolutions.com information and data contained herein are Deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. LG Chem assumes no liability for results obtained or damages incurred

through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. QuantumPure is the Trademark of LG Chem. All rights reserved. © LG Chem, Ltd.