

Nano:H<sub>2</sub>O™



Product Data Sheet

# LG BW 2521 ES

Energy-saving brackish water RO membrane for commercial applications

**Features**

- High permeate flow rate and salt rejection at low feed pressures
- Good durability

**Benefits**

- Low energy consumption
- High permeate water quality

**Ideal Applications**

- Light industrial process water
- Commercial applications


**Performance Specifications**

| Item                      | Unit                              | Value     |
|---------------------------|-----------------------------------|-----------|
| Permeate Flow Rate        | GPD (m <sup>3</sup> /day)         | 345 (1.3) |
| Stabilized Salt Rejection | %                                 | 99.5      |
| Minimum Salt Rejection    | %                                 | 99.2      |
| Active Membrane Area      | ft <sup>2</sup> (m <sup>2</sup> ) | 9 (0.9)   |
| Feed Spacer Thickness     | mil                               | 28        |

The specifications outlined above are normalized performances based on the following test conditions:

- **Test conditions:** 2,000 ppm NaCl, 150 psi (10.3 bar), 25°C (77°F), pH 7, Recovery 8%
- Permeate flow rates for individual elements may vary by ±20%

**Dimensions and Weight**



| Dimensions: mm (in) |              |                |                | Wet Weight: kg (lbs) |
|---------------------|--------------|----------------|----------------|----------------------|
| A                   | B            | C              | D              |                      |
| Element Length      | Element O.D. | Core Tube I.D. | Core Tube Ext. | 1.0 (2.2)            |
| 533 (21)            | 60 (2.4)     | 19 (0.75)      | 32 (1.3)       |                      |

**Operating Specifications**

| Item  | Unit                    | Value      |
|---|-------------------------|------------|
| Maximum Applied Pressure                    | psi (bar)               | 600 (41.3) |
| Maximum Chlorine Concentration              | ppm                     | < 0.1      |
| Maximum Operating Temperature               | °C (°F)                 | 45 (113)   |
| pH Range, Continuous Operation              |                         | 2–11       |
| pH Range, Cleaning                          |                         | 2–12       |
| Maximum Feed Water Turbidity                | NTU                     | 1.0        |
| Maximum Feed Water SDI <sub>15</sub>        |                         | 5.0        |
| Maximum Feed Flow                           | gpm (m <sup>3</sup> /h) | 6 (1.4)    |
| Maximum Pressure Drop (ΔP) for Each Element | psi (bar)               | 15 (1.0)   |



This product is certified to NSF/ANSI/CAN Standard 61 for drinking water systems

The Membrane Elements performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual, which consists of LG Chem, Ltd Technical Service Bulletins ("TSB") and Technical Applications Bulletins ("TAB") and may be viewed and downloaded at [www.lgwatersolutions.com](http://www.lgwatersolutions.com). The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. LG Chem assumes no liability for results obtained or damages incurred through the application of the information contained

herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. NanoH2O is the Trademark of The LG Water Solutions or an affiliated company of LG Chem. All rights reserved. © LG Chem, Ltd.

Please visit our website for regional contact information [www.lgwatersolutions.com](http://www.lgwatersolutions.com)